

Beiblatt zum Sicherheitsdatenblatt / Supplement to the safety data sheet

Abschnitt 1 / Section 1

1.1 Produktidentifikation / Product identification

s. Original-Datenblatt / see original safety data sheet

1.2 Verwendungen des Stoffs / Uses of the substance











s. Original-Datenblatt / see original safety data sheet

1.3 Einzelheiten zum Lieferanten / Details of the supplier

Firmenname /	Supplier	Stürmer Maschinen GmbH,
Straße /	Street	Dr.-Robert-Pfleger-Str. 26,
Ort /	City	D-96103 Hallstadt
Tel. /	Phone	+49 (0)951 96555 - 0 (07:00 - 17:00 Uhr / 07:00 am - 05:00 pm)
E-Mail /	E-Mail	info@stuermer-maschinen.de

1.4 Notrufnummer / Emergency Telephone

Wählen Sie die passende Notrufnummer anhand des GHS-Symbols auf Ihrem Gefahrgut oder entsprechend Abschnitt 2.2 des orig. Sicherheitsdatenblattes *.
Call the appropriate emergency number using the GHS symbol on your dangerous goods or according to section 2.2 of the original safety data sheet *.

GHS Gefahren-piktogramm / GHS symbol	GHS-Kürzel/ GHS-no.	Mögliche Signalwörter/ Warning	Gefährdungsklassen / Description of hazards	Notrufnummer */ Emergency Phone *
	GHS01 bis GHS09			+49 (0)951 96555 - 590 Sammelnotrufnummer Gefahrstoffe
	GHS01	Gefahr oder Achtung / Danger or Attention	Explosive Stoffe/Gemische und Erzeugnisse mit Explosivstoff, selbstzersetzliche Stoffe/Gemische, organische Peroxide / Explosive substances / mixtures and products containing explosives, self-reactive substances / mixtures, organic peroxides	- 591
	GHS02	Gefahr oder Achtung / Danger or Attention	Selbstzersetzliche Stoffe/Gemische, organische Peroxide, entzündbare Gase, Aerosole Flüssigkeiten, Feststoffe, selbsterhitzungsfähige Gemische, pyrophore Flüssigkeiten und Feststoffe, Stoffe/Gemische, die bei Berührung mit Wasser entzündbare Gase bilden / Self-reactive substances / mixtures, organic peroxides, flammable gases, aerosols, liquids, solids, self-heating mixtures, pyrophoric liquids and solids, substances / mixtures which form flammable gases on contact with water	- 592
	GHS03	Gefahr oder Achtung / Danger or Attention	Oxidierende Gase, Flüssigkeiten, Feststoffe / Oxidizing gases, liquids, solids	- 593
	GHS04	Achtung / Attention	Verdichtete, verflüssigte, gelöste und tiefgekühlt verflüssigte Gase / Compressed, liquefied, dissolved and refrigerated liquefied gases	- 594
	GHS05	Gefahr oder Achtung / Danger or Attention	Verätzung der Haut, schwere Augenschäden, auch metallkorrosive Eigenschaften / Chemical burns to the skin, severe eye damage, also metal-corrosive properties	- 595
	GHS06	Gefahr / Danger	Äußerst schwere und schwere akute Gesundheitsschäden oder Tod / Extremely severe and severe acute damage to health or death	- 596
	GHS07	Achtung / Attention	Akute Gesundheitsschäden, Reizung der Haut, der Augen und der Atemwege, Sensibilisierung der Haut, narkotisierende Wirkungen / Acute damage to health, irritation of the skin, eyes and the respiratory tract, sensitization of the skin, narcotic effects	- 597
	GHS08	Gefahr oder Achtung / Danger or Attention	Chronische Gesundheitsschäden (Organschädigungen) bei einmaliger oder mehrmaliger Exposition, krebserzeugende, erbgutverändernde und fortpflanzungsgefährdende Wirkungen, Lungenschäden durch Eindringen von Substanzen in die Lunge (Aspirationsgefahr), Sensibilisierung der Atemwege / Chronic damage to health (damage to organs) after single or multiple exposure, carcinogenic, mutagenic and reproductive effects, lung damage due to the penetration of substances into the lungs (risk of aspiration), sensitization of the respiratory tract	- 598
	GHS09	Achtung oder ohne Signalwort / Attention or without wording	Giftig für Wasserorganismen mit kurz- und langfristiger Wirkung / Toxic to aquatic organisms with short and long-term effects	- 599

* 07:00 - 17:00 Uhr, außerhalb dieses Zeitraums kann die Nummer auf dem Sicherheitsdatenblatt angerufen werden / 07:00 am - 05:00 pm, outside this time, the number on the safety data sheet can be called

Für alle anderen Informationen siehe Original-Sicherheitsdatenblatt / For all other information, see the original safety data sheet

This product is used in a hermetically sealed state. So, it is not an object of the SDS system. This document is provided to customers as reference information for the safe handling of the product. The information and recommendations set forth are made in good faith and are believed to be accurate at the date of preparation. Panasonic Corporation makes no warranty expressed or implied.

PRODUCT SAFETY DATA SHEET

1 Chemical product and company identification

Name of Product : Manganese dioxide lithium battery
Name of Company : Panasonic Energy Co., Ltd.
Address : 1-1 Matsushita-cho, Moriguchi-city, Osaka, 570-8511, Japan
Emergency Contact : +81-80-9932-3190 (JST Working hours)
+81-6-6991-1141 (Holiday)

2 Hazards identification

GHS Classification : No applicable
Toxicity : Vapor generated from burning batteries, may irritate eyes, skin and throat.
Hazard : Electrolyte and lithium metal are inflammable.
Risk of explosion by fire if batteries are disposed in fire or heated above 100 degrees C.
Stacking or jumbling batteries may cause external short circuits, heat generation, fire or explosion.

3 Composition/information of ingredients

Component	Material	CAS RN	Content (%)
Positive electrode	Manganese dioxide	1313-13-9	12 - 50
Negative electrode	Lithium metal	7439-93-2	0.5 - 6
Electrolyte	1,2-dimethoxyethane	110-71-4	1.5 - 3.5
	Lithium Perchlorate	7791-03-9	0.2 - 0.7
	Propylene Carbonate	108-32-7	2.5 - 7
Others (Steel or Plastic parts)	Steel	7439-89-6, 7440-47-3	30 - 85
	Polypropylene	9003-07-0	0.5 - 10

Lithium content per cell

Model Number	Lithium content(g)	Model Number	Lithium content(g)	Model Number	Lithium content(g)	Model Number	Lithium content(g)
CR1025	0.008	CR2012	0.02	CR2330	0.08	CR2412	0.03
CR1216	0.008	CR2016	0.03	CR2354	0.17	CR2430	0.09
CR1220	0.01	CR2025	0.05			CR2450	0.18
CR1612	0.01	CR2032	0.07			CR2477	0.29
CR1616	0.02						
CR1620	0.02					CR3032	0.15
CR1632	0.04						

4 First aid measures (in case of electrolyte leakage from the battery)

- Eye contact : Flush the eyes with plenty of clean water for at least 15 minutes immediately, without rubbing. Get immediate medical treatment. If appropriate procedures are not taken, this may cause eye injury.
- Skin contact : Wash the affected area under tepid running water using a mild soap. If appropriate procedures are not taken, this may cause sores on the skin. Get medical attention if irritation develops or persists.
- Inhalation : Remove to fresh air immediately. Get medical treatment immediately.

5 Firefighting measures

- Fire extinguishing agent : Alcohol-resistant foam and dry sand are effective.
- Extinguishing method : Be sure on the windward to extinguish the fire, since vapor may make eyes, nose and throat irritate, Wear the respiratory protection equipment in some cases.

6 Accidental release measures (in case of electrolyte leakage from the battery)

- Take up with absorbent cloth, treat cloth as inflammable.
- Move the battery away from the fire.

7 Handling and storage

- Handling :
 - ⌘ When packing the batteries, do not allow battery terminals to contact each other, or contact with other metals. Be sure to pack batteries by providing partitions in the packaging box, or in a separate plastic bag so that the single batteries are not mixed together.
 - ⌘ Use strong material for packaging boxes so that they will not be damaged by vibration, impact, dropping and stacking during their transportation.
 - ⌘ Do not short-circuit, recharge, deform, throw into fire or disassemble.
 - ⌘ Do not mix different type of batteries.
 - ⌘ Do not solder directly onto batteries.
 - ⌘ Insert the battery correctly in electrical equipment.
- Storage :
 - ⌘ Do not let water penetrate into packaging boxes during their storage and transportation.
 - ⌘ Do not store the battery in places of the high temperature or under direct sunlight.
 - ⌘ Please also avoid the places of high humidity. Be sure not to expose the battery to condensation, rain or frozen condition

8. Exposure controls and personal protection

Acceptable concentration : Not specified about Lithium Battery.
Facilities : Nothing in particular.

Protective Equipment (in case of electrolyte leakage from the battery)

Respiratory Protection : For most condition no respiratory protection.
Hand Protection : Safety gloves.
Eye Protection : Safety goggle

9. Physical and chemical properties

Appearance : Coin shape
Nominal Voltage : 3 V

10. Stability and reactivity

Since batteries utilize a chemical reaction they are actually considered a chemical product.

As such, battery performance will deteriorate over time even if stored for a long period of time without being used. In addition, the various usage conditions such as discharge, ambient temperature, etc. are not maintained within the specified ranges the life expectancy of the battery may be shortened or the device in which the battery is used may be damaged by electrolyte leakage.

11. Toxicological information

Swallowing can lead to chemical burns, perforation of soft tissue, and death. Severe burns can occur within 2 hours of ingestion. Seek medical attention immediately.

12. Ecological information

In case of the worn out battery was disposed in land, the battery case may be corroded, and leak electrolyte. However, there is no environmental impact information.
Mercury (Hg), Cadmium (Cd) and Lead (Pb) are not used in cell.

13. Disposal considerations

When the battery is worn out, dispose of it under the ordinance of each local government.

14. Transport information

Handling

During the transportation of a large amount of batteries by ship, trailer or railway, do not leave them in the places of high temperatures and do not allow them to be exposed to condensation.

During the transportation do not allow packages to be dropped or damaged.

UN Number, UN Class : UN3090, Class9 (for the Air transport by PI968 Section IA or IB)
: Exemption (for the Marine transport SP188 and the Air transport by Section II of PI 969 or 970)
Even though the cells are classified as lithium metal batteries (UN3090 or UN3091), they are not subject to some requirements of Dangerous Goods Regulations because they meet the following:

1. for cells, the lithium content is not more than 1 g ;
2. each cell is of the type proven to meet the requirements of each test

- in the UN Manual of Tests and Criteria, Part , sub-section 38.3 ;
3. each cell is manufactured in ISO9001 certified factory ;
 4. the test summary is available from ;
<https://industrial.panasonic.com/ww/downloads/battery-test-summary>

Please refer to the following reference information about concrete ways of transportation. Actual content of packaging label and shipping documents varies by shipping companies. Make sure to confirm in advance with your shipping company.

Information of reference

	Reference	Packing Instruction(PI)/ Special provision(SP)	Note
Air transport	IATA DGR	PI 968 Section A	Cells, Cargo Aircraft only; Net quantity per package Max. 35kg
		PI 968 Section B	Cells, Cargo Aircraft only; net quantity per package Max. 2.5kg
		PI 969 Section	Cells packed with equipment
		PI 970 Section	Cells contained in equipment, button cell batteries
Marine transport	IMDG Code	SP 188	

15. Regulatory information

- IATA Dangerous Goods Regulations Edition 64 (IATA DGR)
- IMO International Maritime Dangerous Goods Code 2020 and 2022 Edition (IMDG Code)
- UN Recommendations on the Transportation of Dangerous Goods, Model Regulations
- UN Recommendations on the Transportation of Dangerous Goods, Manual of Tests and Criteria
- EU Battery Directive (2006/66/EC, 2013/56/EU)
- Regulation (EC) No. 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH)
- State of California Regulations - Best management practices for Perchlorate Materials
- Act on Preventing Environmental Pollution of Mercury (Japan)

16. Other information

This PSDS is provided to customers as reference information in order to handle batteries safely. It is necessary for the customer to take appropriate measures depending on the actual situation such as the individual handling, based on this information.

In California only, packages that contain CR lithium coin cells and the Owners/Operating Instructions of products that contain CR lithium coin cells must include the following statement: "Perchlorate Material - special handling may apply,

See <http://www.dtsc.ca.gov/hazardouswaste/perchlorate>".

The effective date for this Perchlorate label is July 1, 2006 for non-consumer products and January 1, 2007 for consumer products.

Prepared by : Engineering Department
Energy Device Business Division
Panasonic Energy Co., Ltd.